

# Liquid Color™ Spot, 12 VAC

www.fountainpeople.com


Model Number: LCS-L

## Product Description:


7.125" diameter by 2.63" high RGB LED underwater fixture; cast copper housing; tempered fritted lens; 120 volt or 12 volt input voltage, 90 watt maximum consumption, integral power supply; Type SE00W Seoprene cord; RGB array to include power line modem module for DMX interface.




## Detail:



Pedestal Mounted



Slab Mounted



Niche Mounted

## Specification:

Beam Angle Options:	10° standard. Options: 8°, 16°, 40°, 16° x 50° elliptical
Total Lumen Output:	1503 Lumens
Color Range:	16.7 million additive RGB colors: continuously variable intensity
Lumen Maintenance:	50% of full output for 50,000 + hours @ 50° C /122°F
Input Voltage:	12VAC 50/60 Hz
Power Consumption:	90 Watts maximum
Control Interface:	DMX and ArtNet. Integral power line modem module.
Control System:	Fountain People, Inc. controller or third-party DMX or ArtNet controller. (LC Series lights allow for up to 170 lights per DMX universe)
Dimensions:	7.125" outer dia. x 2.63" height (181 x 66.8 mm)
Weight:	10.5 lbs. with 10' of cable (4.76 kg)
Housing:	Cast Copper
Lens:	Clear tempered glass with glare and UV screening. Frosted lens optional
Cable Fixture Connection:	Single 10' (3.05 m), 14-3 SE00W cord with long life Seoprene sheathing
Safety Certifications:	ETL per UL676, FCC (Pending), RoHS Compliant
LED Class:	Class 2 LED product
Environment:	Dry / Submerged
Thermal Protection:	Integral Sensor Protection
Mounting Hardware:	Optional: Niche, Freestanding, Custom



fountain people®

Story | Water | Light | Motion

Fountain People, Inc.  
P.O. Box 807  
San Marcos, TX 78666  
T: 512.392.1155  
F: 512.392.1154  
www.fountainpeople.com

Catalog #	
Details	
Project	
Prepared by	
Date	

V1.3