

# Liquid Light™ Spot, 120 VAC

www.fountainpeople.com


Model Number: LLS-H

## Product Description:


7.125" diameter by 2.63" high White 5,300°K LED underwater fixture; cast copper housing; tempered fritted lens; 120 Volt input voltage, 114 watt maximum consumption, integral power supply; Type SE00W Seoprene cord; White array is adjustable for intensity per lighting application.




## Detail:



Pedestal Mounted



Slab Mounted



Niche Mounted

## Specification:

Beam Angle Options:	8°, 26°, 46°, 16° x 50° elliptical
Total Lumen Output:	4,066 @ 5300K (2,741 at optional 3,000°K)*
Lumen Maintenance:	70% of full output for 50,000 + hours @ 50° C /122°F
Input Voltage:	120VAC 50/60 Hz
Power Consumption:	114 Watts maximum (134 Watts with optional 3000K)*
Dimensions:	7.125" outer dia. x 2.63" height (181 x 66.8 mm)
Weight:	10.5 lbs. with 10' of cable (4.76 kg)
Housing:	Cast Copper
Lens:	Clear tempered glass with glare and UV screening. Frosted lens optional
Cable Fixture Connection:	Single 10' (3.05 m), 14-3 SE00W cord with long life Seoprene sheathing (Standard)
Safety Certifications:	ETL per UL676, FCC, CE, RoHS Compliant
LED Class:	Class 2 LED product
Environment:	Dry / Submerged - IP68
Thermal Protection:	Integral Sensor Protection
Mounting Hardware:	Optional: Niche, Freestanding, Custom

## \*Dry Placement Application:

5300K @ 40% Output	1990 Lumens @ 50.3 Watts
3000K @ 30% Output	1118 Lumens @ 44 Watts



fountain people

Story | Water | Light | Motion

Fountain People, Inc.  
P.O. Box 807  
San Marcos, TX 78666  
T: 512.392.1155  
F: 512.392.1154  
www.fountainpeople.com

Catalog #	
Details	
Project	
Prepared by	
Date	

V1.6